

## **CX-7A** Key Features, Specification

Best for narrow, short barcodes.

Special design, never block barcodes.

Button line align barcode, it scans.

ABS trigger, easy to push.

Lighter weight, better efficiency.



## Specifications:

Model No.	CX-7A
Decoding	Fuzzy-logic decoder
Capability	
Light Source	Red LED (wavelength 660nm)
Scan Speed	100 scan/second
Depth of Field	0 ~ 30 mm
Resolution	≥ 0.127 mm
Print Contrast	0.3 minimum
Readable Codes	UPC/EAN/JAN and Add-on 2/5, Code 39, Code 128,
	Codabar, ISBN, Standard 2 of 5
	ISSN, China Postage, ITF 2 of 5, MTX 2 of 5, IND 2 of 5,
	Code 4, Code 11, Code 93, Code IV, MSI/Plessey
Interface Types	K/B wedge, RS-232, USB, (OCIA is optional)
Standard connectors	USB, Keyboard Wedge, RS232
Power Requirements	5V DC <u>+</u> 10%
Power Consumption	100 mA (scanning), 48 mA (stand-by)
Operating	0 < T < 45°ℂ (Ambient)
Temperature	
Drop Durability	1.7 m drop to concrete
Certifications	FCC B class and CE
Dimension	175 (L) x 84 (W) x 38 (H) mm
Case Material	ABS (BLACK color)
Weight	100 g (without cable)

