

UTK3000自助結帳機

- 工業級品質：
採用工規高品質元件，確保長時間穩定運行，
適合各種餐飲業嚴苛環境。
- 人體工學設計：
配備23.8" 符合人體工學尺寸觸控面板，
提供舒適直觀的操作體驗。
- 靈活配置：
依不同應用場景彈性配置各種周邊設備，
滿足多樣化需求。
- 共用設計：
可延伸不同現金功能桌上及落地式設計，簡化後續維護並降低維運成本。



Specifications

SKU	x86	
Processor System	Processor	Intel® N97 Intel® i3-N305
	Memory	up to 16G DDR5-4800 SODIMM *1
	Storage	M.2 M-key 2280 x 2
	Bluetooth	Bluetooth® 5.0
	Network (WLAN)	LAN1, 2 - i226: up to 2.5 Gbps
	Network (LAN)	1 x 10/100/1000 Mbps
Outlook	Stereo Speaker	3W x 2
	Dimension	23.8": 400 x 300 x 948 mm 27": 400 x 300 x 1026 mm 32": 400 x 300 x 1131 mm Stand: 700 x 500 x 870 mm
	Weight	23.8": 22.5 Kg 27": 28.5 Kg 32": 36 Kg Stand: 37 Kg
Touch monitor	Size/Type	23.8"; 27"; 32" TFT LCD with Projected capacitive touch
	Brightness (cd/m²)	250 nits; 500nits (optional)
	Resolution	1920 x 1080 max.
	Color	16.7 M
	Contrast	23.8": 1000:1; 27", 32": 3000:1
	View Angle	178° H/V
	Light Transmission	80% ± 3%
	Controller	USB interface
OS support	Operating system	Android 10 Windows 10 / Windows 11
Environmental Specifications	Operation Temperature	0 ~ 40 °C / 32 ~ 104 °F
	Relative Humidity	10 ~ 95% @ 40 °C / 104 °F non-condensing
Power Supply	Printer	100-240V 48W 24V / 2.0A
	BOX PC and Touch monitor	100-240V 84W 12V / 7A
Peripherals	Printer	58mm/80mm thermal printer
	Scanner	Embedded 1D/2D scanner module
	RFID	13.56MHz non-contact radio frequency
	Camera and MIC	8M auto focus camera with microphone module
	LED Indicator	RGB 3 color light



Vectronix System Inc. <http://www.vectronix.com.tw>

TEL:886-2-8227-3177 FAX:886-2-8227-3167

4F.-1, No.268, Liancheng Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)